

STRUCTION MANUAL
ODE D'EMPLOI
EBRUIKSAANWIJZING

JUMBO



©



www.haminternational.eu

Specifications

General

Channels	120 channels in 3 bands
Modulation Modes	FM, AM, LSB, USB
Frequency Range	26.965 to 28.305 MHz
Tune	±5 kHz
Frequency Control	Phase-locked synthesizer
Frequency Tolerance	±0.005%
Frequency Stability	±0.003%
Operating Temperature Range	-30°C to +50°C
Microphone	Plug-in [4-pin], 600 Ohm dynamic type
AC Input Voltage	220V, 50/60 Hz
AC Power Consumption	75W
DC Current Drain	1.5A [at maximum audio modulation] 0.5A [at standby with no signal]
Antenna Connectors [A and B]	Standard SO-239 type
Semiconductors	6 ICs, 2 FETs, 52 Transistors (Excluding the <i>Roger Beep</i> unit)
Meter #1	Indicates relative RF power output/antenna SWR,
Meter #2	Indicates received signal strength

Transmitter

Power Output	4W or 0.5W—AM/FM, 12W (PEP)-Single sideband
SSB Generation	Dual-balanced modulation
AM Modulation	Class B amplitude, collectors modulation
AM Modulation Capability	100%
Harmonic and Spurious Emission	Better than 60 dB
AM/FM Frequency Response	400 to 5,000 Hz
SSB Frequency Response	400 to 3,000 Hz
Output Impedances [A and B]	50 Ohms unbalanced
Output Indicators	RF Meter shows relative RF output power
Tune	±4.5 kHz minimum

Receiver

FM Sensitivity	0.5 µV for 20 dB S/N
AM Sensitivity	0.7 µV for 10 dB S/N
SSB Sensitivity	0.2 µV for 10 dB S/N
AM/FM Selectivity	5 dB at 4 kHz, 50 dB at 10 kHz
SSB Selectivity	5 dB at 2 kHz
Image Rejection	More than 50 dB
IF Rejection	More than 80 dB at 455 kHz
AGC	Change in audio output: less than 12 dB from 10 µV to 0.4V
Squelch	Adjustable – threshold less than 0.7 µV
Audio Frequency Response	400 to 2,500 Hz
Distortion	Less than 10% at 3 watts output 8 Ohms
Adjacent Channel Rejection	>75 dB at 0.3 µV
Cross Modulation	>50 dB
Intermediate Frequency	10.695 MHz [AM-1st, SSB], 455 kHz [AM-2nd]
Clarifier Range	±800 Hz
Tune Range	±4.5 kHz minimum
Noise blanker	IF single gate type
Audio Output Power	More than 3 watts into 8 Ohms
Built-in Speaker	8 Ohms, dynamic
External Speaker (optional)	Disables internal speaker when connected

General Description

The *HAM International JUMBO* is an advanced FM/AM/SSB 2-way transceiver primarily designed for base station operation. It employs the very latest technology to provide 120 channels operation for 3 modes of transmitting and receiving by means of the phase-locked loop (PLL) circuitry. The use of the PLL circuitry assures a precise on-frequency operation on every channel that is unmatched by conventional frequency synthesis system units. The *JUMBO* also features the following:

- "Roger Beep" built-in.
- Electromagnetic TX-RX switching enables selective call facility.
- Two relay switched antenna inputs.
- Tune facility allows between-channel operation specially in SSB with more convenience than VFO.
- RF power (4W/0.5W) switch provided.
- Optional: Table pre-amplified compressor microphone model *TW232S* from *Ham International*.
- 120 channels in 3 bands.
- Modulation control lamp.
- Output for frequency counter.
- Giant LED's assures bright channel display.
- Detachable handgrips for professional 19" rack mounting.

Description Générale


L'émetteur-récepteur *JUMBO* de *HAM International* utilise les techniques les plus avancées dans le domaine des radio-communications. On y trouve les innovations techniques les plus récentes tel que la modulation de fréquence à déviation étroite, les 120 canaux continus produit par circuit intégré à fonction logique (PLL) ainsi que la commutation électronique émission-réception. Le *JUMBO* offre aussi les nouveautés suivantes:

- *Roger Beep* incorporé.
- Connecteur prévu pour l'utilisation d'un appel sélectif Ham International.
- 2 entrées d'antennes commutable par relay.
- Le bouton "TUNE" permet aussi d'opérer sur tous les canaux intermédiaires spécialement en SSB avec plus de confort qu'un VFO.
- Switch sortie RF (4W/0.5W) prévu.
- En option: Le micro de table pré-amplifié à compresseur, le modèle *TW232S* de *Ham International*.
- 120 canaux divisés en 3 bandes.
- Lampe de contrôle de la modulation.
- Sortie pour compteur de fréquence.
- Diodes électro-luminescentes géantes pour affichage digital très lisible.
- Poignées détachables pour montage en rack professionnel 19".

Algemene Beschrijving

De *HAM International JUMBO* is een technisch ver gevorderde FM/AM/SSB zenderontvanger ontworpen met het oog op een gebruik hoofdzakelijk als basisstation. De laatste technologische snufjes werden gebruikt om 120 kanalen voort te brengen door middel van digitale frekventie syntese met Phase lock loop (PLL circuits). Deze PLL schakeling verzekert een nauwkeurige frekventie van ieder kanaal, in alle modes. Dit systeem is wat betreft kwaliteit niet te evenaren door de konventionele kristal synthesizers. De *JUMBO* heeft boven dien een aantal uitzonderlijke extras.

- 120 kanalen in 3 banden
- Ingebouwde Roger Beep
- Aansluiting voor selektieve systemen
- 2 omschakelbare antenne aansluitingen (vb beam + GP)
- Tuning welke toelaat tussen de kanalen te worden vooral in SSB gemakkelijker dan met een VFO
- RF vermogen (4W/0.5W) schakelaar voorzien.
- Controle lamp voor de modulatie
- Aansluiting voor frekventie teller
- Zeer heldere kanaalaanduiding met reuze led display
- Met Professionele afneembare bandvaten voor montage in een HIFI RACK (19 inch)
- Bijbehoren tegen meerprijs te bekomen van *Ham International* – *TW232S*: Top kwaliteit tafel mikrofoon met ingebouwde kompressor voorversterke.



* See page 7.

Installation

Connection

The transceiver is supplied with AC power cord. Proceed as follows to complete all necessary connections to the transceiver:

1. Your transceiver has two standard antenna connectors of type SO-239 located on rear panel, for easy connection to standard PL-259 coax plugs. Use only enough cable to suit your needs. This will insure a proper impedance match and maximum power transfer from the transmitter to the antenna. If the coax antenna cable must be made longer, use coax cable with high efficiency and quality such as type RG-8/u.
2. *AC Power Operation:* Use 220 volts AC power for base station operation. Plug AC power cord into a working 220 volts household outlet.

Noise Interference

There are several kinds of noise interfering you may encounter in base station operation. Some of these noise sources are; fluorescent buzz, nearby commercial broadcast, electrical appliance, lawnmower, and electrical storms, etc. Commercial products are available to reduce interference from these sources. Consult your dealer or CB/amateur radio supply shops.

Antennas

Ham International has designed a high power antenna for best performance in local and DX use with large bandwidth for equal quality on 120 channels:

The Superstar.

Remote Speaker

The external speaker jack (EXT. SP) on the rear panel is used for remote receiver monitoring. The external speaker should have 8 ohms impedance and be able to handle at least 3 watts. When the external speaker is plugged in, the internal speaker is disconnected.

Instal

Conn

Procédez aux connections dans l'ordre suivant:

1. Votre Jumbo est équipé sur le panneau arrière de deux connecteurs d'antenne du type SO-239 qui conviennent pour les fiches standard PL259. Utilisez du cable coaxial de 50 ohms pour vos rallonges d'antennes.
2. *Utilisation sur le secteur AC 220V*
Connecter le cable d'alimentation AC dans la prise prévue à cet effet sur le panneau arrière et l'autre extrémité dans une prise de courant 220V.

ANTENNAS

HAM INTERNATIONAL a prévu pour votre Jumbo une antenne de base de haut rendement avec une large bande passante pour un résultat optimal en local ou en DX sur les 120 canaux: le modèle SUPERSTAR.

Plaatsing

Aansluitingen

1. Deze zenderontvanger heeft twee antenne aansluit mogelijkheden op het achterpaneel. Gebruik uitsluitend kabel van 50 ohm en de klassieke PL259 Plugs (amphe-nols).

2. *Gebruik op 220V netspanning*
Sluit het overeenkomstige snoer op de AC aansluitplug en op het stopkontakt 220V.

Antennes

Ham International heeft voor uw JUMBO een bijpassende antenne met hoog rendement en een grote bandbreedte voor een maksimum resultaat zowel voor lokaal als voor DX: De Superstar.

Control Function

1 Power Switch

Place in POWER (lever up) position to apply power to the unit.

2 Noise Blanker Switch

This switch activates the noise blunker circuit when placed in NB (lever up) position. The noise blunker is very effective for repetitive impulse noise such as ignition interference.

3 ANL Switch

When this switch is placed in the ANL (lever up) position, the automatic noise limiter in the audio is activated. The ANL may be used when noises generated from such sources as atmospheric discharge, electronic machinery etc., are present.

4 RF Power (4W/0.5W) Switch

Permits you to adjust the RF output when AM/FM transmitting – 4W or 0.5W.

5 High Filter Switch

This switch is used to remove high frequency noise from received signal.

6 SWR-Calibrate Switch

This switch serves for SWR check of your antenna:

CALIB (lever down): Used to calibrate the SWR meter before measuring your antenna's SWR ratio.

SWR (lever up): Used to directly read the SWR of antenna connected to the unit. See *SWR check*.

7 Calibrate Control

This control is used for calibrating the SWR meter for accurate SWR measuring in conjunction with the *SWR-CALIB Switch 6*.

8 Tune

In pulled position, allows to vary the operating frequency with plus minus 4.5 kHz and functions as a VFO. In pushed position, the frequency is the center frequency of the channel displayed.

9 RF Gain Control

This control is used primarily to optimize reception sensitivity in strong signal areas. Under normal operating conditions the control should be turned fully clockwise. When strong overload or distorted signals are received rotate this control counterclockwise to reduce gain.

Note: The *Squelch Control 15*) may require readjustment with reduced *RF Gain Control*.

Face Avant

1 POWER

Placer ce switch en position power pour alimenter l'appareil.

2 NB

Met le filtre "noise blunker" incorporé en fonctionnement pour atténuer seulement les parasites tel que ceux produit par les moteurs à explosion.

3 ANL

Met le filtre "ANL" incorporé en fonctionnement pour atténuer les bruits de fond pendant la réception.

4 Switch Sortie RF (4W/0.5W)

Controle le niveau sortie RF en émission MA/MF – 4W ou 0.5W.

5 HI-FI

Cet interrupteur permet de diminuer les sous aigus indésirables signaux reçus.

6 SWR/Calibrate

- En position *CALIB*: Pour calibrer le Tos-mètre avant la mesure du TOS.
- En position *SWR*: Lecture du TOS sur le Tos-mètre.

7 Calibrate

Permet de calibrer le TOS-mètre lorsque l'inverseur SWR-CALIB est en position *CALIB*.

8 Tune

- En position tirée, ce bouton, permet de varier la fréquence d'opération de ±4,5 kHz par rapport à la fréquence du canal indiqué.
- En position poussée le tune ne fonctionne pas.

9 RF Gain

Pour atténuer les signaux trop puissance en réception; sa position normale est la position maximale à droite.

10 MIC Gain

Un circuit pré-amplificateur pour le micro est incorporé dans votre JUMBO et permet une adaptation optimale à vos conditions de transmission.

11 Channel

Le bouton permet de déterminer le canal d'opération en combinaison avec le sélecteur de bande.

12 Mode

Le bouton détermine le mode de modulation soit:

FM: Fréquence modulée à déviation étroite.

AM: Modulation d'amplitude.

Voorzijde

1 Power

Plaats deze schakelaar in de positie *POWER* om het toestel aan te schakelen.

2 NB

Plaats de schakelaar omhoog om de Noise Blunker in te schakelen. Deze is alleen effectief om korte repeaterende stoorpulsen zoals ontstekingsstoring van wagens te verminderen.

3 ANL

De schakelaar omhoog stelt de automatische ruis en storingsonderdrukker in werking in het audio degeelte, nuttig om atmosferische en allerhande storingen te onderdrukken. Gewoonlijk wordt hij continu ingeschakeld.

4 RF Vermogen Schakelaar (4W/0.5W)

Regelt de AM/FM zendvermogen bij de zenden – 4W of 0.5W.

5 HI FIL

Met deze schakelaar kan men scherpe tonen tijdens de ontvangst wegsnijden.

6 SWR-Calibrate

In de positie *Calib*: om voor het meten van de staande golfverhouding de meter in te stellen. In de positie *SWR*: aflezing van de staande golf verhouding(SWR).

7 Calibrate

Hiermee regelt men de naald van de SWR meter op set terwijl de *SWR/Calib* schakelaar in de stand *Calib* staat.

8 Tune

Als men de knop uitstrekt kan men zowel zend als ontvangst frequentie ±4,5 kHz bijregelen als de knop ingedrukt is krijgt men automatisch de juiste kanaalfrequentie.

9 RF Gain

Om te sterke signalen bij ontvangst af te zwakken deze regeling staat normaal op maximum (wijzerzin) = minimum verzwakking.

10 Mic Gain

In de *JUMBO* is een microfoon voorversterker ingebouwd, deze regelaar laat toe elke microfoon of stem optimaal aan te passen.


11 Channel

In samenspel met de bandschakelaar kan men hiermee elk gewenst kanaal kiezen.

- 10 Microphone Gain Control**
A preamplifier circuit is built into this unit to increase microphone gain. Experiment with this control for the setting that will best suit your individual use.
- 11 Channel Selector**
This control selects any one of the 120 citizens band channels desired. The selected channel is digitally displayed in the window directly above the control.
- 12 Mode Selector**
This control selects the mode of operation in either FM, standard AM, upper sideband, or lower sideband. Transmission in a mode can only be communicated to stations operating in the same mode.
- 13 Antenna A-B Selector**
For switching between two types of antennas or dummy load that may be connected to the unit. You may connect a ground plane antenna (non-directional) to Antenna A receptacle, and a beam type antenna (highly directional) to the Antenna B receptacle on rear panel for long-range communications.
- 14 Band Selector (HI-MID-LOW)**
This is used in conjunction with the *Channel Selector* and selects one of 3 bands which are composed of 40 channels. Setting this to *Low* position enables you to operate over channels 1 through 40; *MID* position channels 41 to 80; and *Hi* position channels 81 to 120.
- 15 Squelch Control**
This control is used to cut off or eliminate receiver background noise in the absence of an incoming signal. For maximum receiver sensitivity it is desired that the control be adjusted only to the point where the receiver background noise or ambient background noise is eliminated. Turn fully counterclockwise then slowly clockwise until the receiver noise just disappears. Any signal to be received must now be slightly stronger than the average received noise. Further clockwise rotation will increase the threshold level which a signal must overcome in order to be heard. Only strong signals will be heard at a maximum clockwise setting.
- 16 AF Gain (Volume) Control**
Permits you to adjust the listening level when receiving.
- 12 Mode**
Hiermee kann een der modulatie soorten gekozen worden.
FM: Frekventie modulatie met heel smalle zwaai.
AM: Amplitude modulatie.
LSB-USB: Enkelzijband modulatie (SSB).
LSB = Lage zijband.
USB = Hoge zijband.
- 13 Antenne A en B**
Mogelijkheid tot 2 antennes gelijktijdig aan te sluiten en met de schakelaar in een oogwenk om te schakelen vb. van Horizontaal naar verticaal.
- 14 Band selector**
Stand *L* geeft de kanalen 1 tot 40. Stand *M* geeft de kanalen 41 tot 80. Stand *H* geeft de kanalen 81 tot 120. (Opgepast sommigen van deze laatste vallen in de 10m amateurband).
- 15 Squelch**
Hiermee kan men het vervelende achtergrond geruis bij afwezigheid van uitzendingen, of het lawaai van zwakke ongewenste stations wegwerken.
- 16 Volume**
Regelt de geluidssterkte bij de ontvangst.
- 17 Clarifier (Fijnregeling)**
Deze regeling laat toe de ontvanger af te stemmen op uitzendingen welke niet op de juiste frequentie zijn. In SSB wordt deze gebruikt om de juiste toonhoogte van de klank te verkrijgen voor een natuurgetrouwere weergave. De clarifier is slechts ingeschakelt als de knop uitgetrokken is. In *Duw* positie is de ontvangst frekventie gelijk aan de zendfrekwen tie en werkt de clarifier niet.

17 Clarifier

The clarifier works only in pulled position. In pushed position the clarifier does not operate and the frequency of the receiver is same as the transmitter.



Rear Panel

1 220V AC Power Cable.

2 Fuse

1A, 250V.

3 External Speaker Jack

For 8 Ohm external Speaker connection. When the plug is inserted to this jack, the internal speaker is silenced.

4 Selective Call Jack

Used to connect the optional selective call unit (available from Ham International).

5 Antenna Connectors A/B

Used to connect antennas to the unit and mate with 50 Ohm coaxial plug, type PL-259.

6 Frequency Counter Output.

Face Arrière

1 Cable d'alimentation 220V AC.

2 Fusible

1A, 250V.

3 Connecteur ext. sp.

Pour connecter un haut-parleur extérieur de 8 ohms. En introduisant la fiche, le HP intérieur est mis hors circuit.

4 Connecteur Sel Call

Prévu pour connecter un système d'appel selectif HAM International.

5 Connecteur d'antenne A et B

Prévu pour connecter le cable coaxial 50 ohms par l'intermédiaire d'une fiche PL259.

6 Sortie pour fréquence-mètre.

Achter Zijde

1 Aansluitsnoer voor AC 220V.

2 Fuse

Zekering 1A, 250V.

3 Ext. Sp.

Aansluitbus voor extra luidspreker, de inwendige luidspreker wordt bij het insteken van een plug uitgeschakeld.

4 Selectief Call

Aansluiting, vraag raad aan uw Ham international verdeler.

5 Antenne aansluitbussen A en B

6 Uitgang naar frek wentie meter

Indicators

See page 3.

1 Signal Strength Meter

The left hand meter provides a relative indication of the signal strength of a received signal in S units during reception. Note that SSB signals will respond this meter only during voice modulation. This being due to the fact that SSB transmissions do not contain a continuous RF carrier as is found on AM or FM.

2 RF Power/SWR Meter

Used for two purposes – to indicate relative transmitter power (4W or 0.5W AM/FM – selectable, 12W PEP SSB) when transmitting; to indicate the antenna SWR [standing wave ratio].

3 Channel Display

This is an LED [light emitting diode] digital readout which indicates the channel selected by the *Channel Selector 11*.

4 Function Indicators

The LED indicators located in this area permit you to know instantly the mode with which the unit has been engaged.

Hi-CH: Lights up when unit is operating in *Hi* 40 channels.

On Air: Lights up during transmit mode indicating you are on-the-air.

Modulation: Lights up during transmitting with intensity varied according to the strength of your voice modulation.

FM, AM, SSB: Indicates a mode selected by the *Mode Selector 12*.

Push-to-Talk

Microphone

The receiver and transmitter are controlled by the *Push-to-Talk* switch on the microphone. Press the switch and the transmitter is activated; release the switch to receive. When transmitting, hold the microphone two inches from the mouth and speak clearly in a normal voice. The radio comes complete with the low impedance dynamic microphone supplied.

Optional: TW232S table microphone.

Operating Procedure

To Receive

Important: Make sure antenna, power source, and microphone are connected before you operate.

- 1 Turn the unit on by setting the *Power Switch 1*) to *On* position. Now the meters, *Channel Display* and *Function Indicator* will be illuminated.
- 2 Temporarily, set the *Mode Selector 12*) in *AM* position.
- 3 Set the *Squelch Control 15*) in fully counterclockwise position and adjust the *AF Gain control 16*) for a comfortable listening level.
- 4 Listen to the background noise from the speaker. Turn the *Squelch Control 15*) slowly clockwise until the noise just disappears (no signal should be present). Leave the *Squelch Control* at this setting. The *Squelch Control* is now properly adjusted. The receiver will remain quiet until a signal is actually received. Do not advance the *Squelch Control* too far clockwise or some of the weaker signals will not be heard.
- 5 Set *Tune* and *Clarifier* in the pushed and center position respectively.
- 6 Select a desired mode of operation, *FM*, *AM*, *SSB*, or, *USB*. Adjust *Clarifier 17*) for advanced operation.

To Receive

- 1 Select the desired channel and mode of transmission.
- 2 If the channel is clear, depress the *Push-to-Talk* switch on the microphone. Speak in a normal tone of voice.

SWR Check

Though most antennas are factory-tuned, adjusting the length of antenna using the SWR meter may peak the antenna efficiency and protect the final RF power transistors from an overload due to mismatch. Proceed as follows:

- 1 Set the unit in the receive mode as instructed under the Operating Procedure to Receive section.
- 2 Set the Mode switch 12) to AM position; the SWR-Cal 6) switch to the Cal position.
- 3 Pressing the Push-to-Talk switch on the microphone and turn the Calibrate Control 7) clockwise (past click) so that the SWR meter pointer exactly coincides with the Set mark on the scale. Release the Push-to-Talk switch.
- 4 Set the SWR-Cal switch to the SWR position and depress the Push-to-Talk switch again. The SWR of your antenna is read directly on the scale. An SWR below 2 or less is desired as this indicates that over 95% of the transmitted power is broadcast into the air.

Note: If you find difficulty to obtain SWR readings smaller than 3 (ratio 1 is ideal though very hard to gain), consult the dealer to determine how to match your antenna to your *JUMBO*.


Maintenance and Adjustment

The transceiver is specifically designed for the environment encountered in the base station use. The use of fully solid state circuitry and its rugged style result in high reliability. Should a failure occur, however, replace parts only with identical parts. Do not substitute. Refer to the Schematic Diagram and Replacement Parts List in this manual. If the performance described in the *Operation* section is not obtained, review the *Installation* section to insure that proper procedures were followed. If a problem still exists, refer to your *HAM International* dealer.

Circuit Description

The transceiver is a 120 channel CB radio which uses a phase locked loop [PLL] system of frequency synthesization to produce the crystal controlled channel and IF signals used in operation of the transmitter and receiver sections of the unit. The basic PLL system is comprised of a free-running voltage controlled oscillator (part of IC2), a phase detector, a reference crystal oscillator (Q3) and a programmable divider (IC1), as seen in diagram below.

PLL Theory (PTOS006 Circuit Board)




The voltage controlled oscillator [VCO] operates in the frequency range of 17.5550 to 18.4450 MHz in the AM/FM/USB mode and 17.5535 to 18.4435 MHz in the LSB mode, and is used to produce two output signals: #1; 37.660 to 39.000 MHz in the AM/FM/USB mode and 37.657 to 38.997 MHz in the LSB mode, #2; at 2.55 to 2.11 MHz. Reference frequency oscillator Q4 oscillates at 10.0525, 10.165, or 10.2775 MHz in accordance with the Band Selector switch (1.5 kHz lower when LSB mode). Its output is fed through the band-pass filter [BPF]/doubler resulting in an output signal, 20.105, 20.33, or 20.555 MHz in accordance with the band selected (3 kHz lower when LSB mode). This signal beats with the VCO free-running signal producing a 37.66 to 39.0 MHz in the AM/FM/USB mode and 37.657 to 38.997 MHz in the LSB mode, which is fed to the receiver first mixer [Q22] and also to IC3 (on main circuit board PTBM059), the transmitter mixer. The second VCO output signal, at 2.55 to 2.11 MHz is fed to the programmable divider in IC1. Simultaneously the 10.24 MHz output of Q3 [through the buffer Q2] is applied to the programmable divider in IC1 and is divided down in 10 kHz steps. As a channel is chosen by the Channel Selector switch [SW-1 on PTS-W076], and N code signal is applied to the terminals [pin No. 9 to 15 of IC1] on the programmable divider in IC1, to preset the divider. The two signals, the crystal oscillated signal [10.24 MHz] from Q3, and the signal from the VCO via the lowpass filter [LPF] and buffer [in the IC1], are compared in the phase detector of IC1 and the phase detector produces a DC output voltage derived

from the phase difference in the signals fed to it. This DC output is applied through an LPF to the VCO, forming the phase loop. This DC voltage applied to the VCO causes it to shift frequency until its output signal locks up with the count-down frequency provided from reference oscillator Q3 [when two signals are in phase] at which point no DC output is produced in the phase detector, and the VCO remains *locked* on frequency. When a new channel is selected a new *N* code is applied to the programmable divider. The VCO is no longer locked because of the resulting phase difference in the phase detector, and it again shifts frequency to a locked condition, in turn producing 37 MHz output signals corresponding to the new channel programmed by the new *N* code. In summary it will be seen that a stable VCO frequency range will be produced, each specific frequency being determined by the *N* code selected by the Channel Selector switch.

Main Board Assembly (PTBM059)

The crystal oscillator Q12 is operating at 10.695 MHz in the AM/FM/USB mode, and 10.692 MHz in the LSB mode, controlled by the crystal, X3. This signal is #1; in the AM and FM modes of transmission, fed to the IC3 to be mixed with the first TX local oscillator frequency and result in 27 MHz transmitter frequencies, and #2; in the SSB modes of transmission, modulated through the balanced modulator IC4 with the audio output signal from the microphone amplifier, IC5. The resultant output of the balanced modulator is a double sideband, suppressed carrier signal. The crystal filter, XF, pass band is restricted to 3.5 kHz so that it allows only one sideband to pass through its output terminals, either USB or LSB mode, depending upon the Mode Selector switch selection. The exact frequency of which was determined by the Channel Selector switch selection and the PLL circuitry, as previously outlined, the resultant frequency, therefore, that is fed to the RF amplifier in IC3, is the channel frequency on the channel selected [channel 1 through 120 over 26.965 to 28.305 MHz]. The 27 MHz RF amplifier output is coupled to RF predriver transistors, Q7, 8, through T4, 5. The predrivers serve to isolate the oscillator and mixer stages from the output amplifiers, and at the same time provide a certain amount of power gain. Q8 output is applied to the base input of Q9, the RF driver stage and in turn to the Q10, the RF power output stage of the transmitter. These stages amplify the 27 MHz RF signal resulting in an output at L13 of 4W (or 0.5W) in AM or FM mode, and 12 watts PEP [peak envelope power] in the SSB mode.

TX Diagram



Modulation Circuit

AM: The microphone feeds voice audio through Q701 on PTSW072 to the power audio IC IC5, and finally to collectors of Q9 and final RF power amplifier Q10 through T16, thereby amplitude modulating the carrier in AM transmission.

FM: In the FM mode, IC5 output is led to the anode of the FM modulating variable capacitor D5 (also involved for 'Tune' control) in circuit board assembly PTOS006, varying its bias to change parallel capacitance to X2, X3, or X4, finally giving deviation to PLL output frequency.

SSB: The IC5 output is directly fed to the balanced modulator IC4, resulting in suppressed carrier double side band, which is in turn supplied to the crystal filter to carrier removal.

ALC: An audio ALC [automatic level control] voltage derived from the audio signal at Q35 is fed to IC5 to control the output of audio amplifier to prevent overmodulation. In the AM or FM transmission, the output of Q35 is led to Q37 and is used to control the output of T16, whereas in the SSB transmit mode, the output of Q35 is fed to Q38 and is connected to the primary side of T16. This being due to the fact that the output of IC5 [modulation signal] is fed [to modulate the RF signal] from the secondary side of T16 in the AM or FM mode, and from the primary side of T16 in the SSB mode of transmission.

The transceiver is also equipped with the RF ALC circuit utilizing the RF output induced at the input of L12 [in the SSB mode only]. The minus voltage detected through D8 is applied to the DC

plus bias circuit [pin number 7 of IC3, TX mixer] thus reducing the gain of the TX mixer as high level RF signal is observed at L12. This circuit is disabled in the AM or FM mode of transmission. In summary, the ALC circuit [both audio and RF] accomplishes very important function, not only preventing overmodulation, but in the view of harmonic and spurious suppression [especially in the SSB transmit mode].

Antenna Transmission Line

The lowpass filter between the antenna and collector of Q10 serves to pass the 27 MHz signals, attenuating higher frequency signals. It also acts to match the antenna impedance to the output impedance of the transmitter output stage, this nominally being 50 Ohm.

Receiver


The RF signal, at a frequency between 26.965 to 28.305 MHz, feeds from the antenna through L13, 12, 11, and T7 to the 27 MHz RF amplifier Q20. Then the amplified output signal from Q20 is coupled through T9 to first mixer Q22 where it is beat with an injection signal from the VCO, IC2, through the VCO buffer Q2.

The frequency of the injection signal from IC2 depends on the channel being selected, as a signal of the 37 MHz range is programmed by the Channel Selector. The output of Q22 is therefore, 10.695 MHz in the AM/FM/USB modes, and 10.692 MHz in the LSB mode, the first intermediate frequency and is the result of the RF input and mixing of IC2 VCO signals.

In case of the AM or FM receive mode, this 10.695 MHz first IF signal is then fed to the second mixer, balanced D22 and D23. Also fed to the second mixer is the second local oscillator signal, 10.24 MHz, from Q3. Mixing of these two signals result in a signal at a frequency of 455 kHz in T14. This is the second intermediate frequency for AM or FM mode of reception. In AM mode, the 455 kHz signal passes through the ceramic bandpass filter CF, and fed to IF amplifiers Q27, 28, and 29, which include IF transformer T15. The output of Q29 is applied to D25, the AM diode detector, while in FM receiving mode, the 455 kHz signal amplified only through Q27 is led to FM demodulating IC, IC3 on the PTOS006 through T4. Resultant demodulated audio is achieved from the IC pin #12 and input to AF gain control VR, VR1. In the SSB mode of reception, the signal obtained as a result of the mixing of the RF input and IC2 VCO signals, 10.695 MHz in the USB, and 10.692 MHz in the LSB mode, is not converted down to lower intermediate frequency, but is passed through the crystal filter, XF, and fed to the SSB IF amplifiers, Q14, 16, and 17, which includes T11, and 12. The signal at the secondary side of T12 is fed to Q19, the product SSB detector and beat with the BFO [beat frequency oscillator] signal from the Q12 and finally rectified to audio frequency signal.

The audio signal output from detectors (for AM [D25], FM [IC2], and SSB [Q19]), is passed through the AF Gain Control, VR1, to the input of the audio amplifier, IC5. The audio output is transformer-coupled to the internal speaker, or to an external speaker through External Speaker jack, J3.

RX Diagram



Squelch

Q32, 33, and 34 are the squelch amplifier transistors. At low [or no] signal levels Q34 collector conducts to ground and its output connected to pin number 6 of IC5 results in no signal output from the audio amplifier. As the incoming RF signal increases it results in opening up the AF amplifier and output is activated. The point at which Q34 cuts off is determined by setting of the Squelch Control, VR2.

Noise Blanker

The noises contained in the RF signal at the output of RF amplifier, Q20, is fed through C112 to the base of Q23. The amplified signal output of Q20 is rectified by diodes D20 and 21. The resulting DC voltage turns on Q24 [FET] which in turn turns on Q25 and 26. This causes the IF signal [10.695 or 10.692 MHz] at T10 to be conducted to ground through C121 and Q26 during the presence of the noise impulses, blanking out the noise from the audio output.

'Tune' Circuit (PTOS006)

The 'Tune' control facility allows between-channel operation shifting both the transmit and receive frequencies 4.5 kHz above or below the assigned channel frequency continuously.

The active elements of the circuit are variable-capacitance diodes D4, D5 and VR4. Both diodes capacitances vary in accordance with the bias level determined by VR4 adjustment, thus increasing or decreasing the parallel capacitance to R14 at Q4 emitter through C25 (by D4) and the external capacitance to X1, X2 or X3 (by D5) simultaneously. The bias of both diodes is fixed when VR4 is pulled to *Off*.

Clarifier Circuit

The Clarifier is operative only in receive mode and changes the receive frequency regardless of the transmitting frequency. VR6 acts to vary the plus bias voltage of D206 (on circuit board Y3) in the same way as in Tune circuit description. Thus, Q4 oscillating frequency is pulled above (VR6 clockwise rotated) or down (VR6 counterclockwise rotated) its normal channel frequency. D206 is fixed biased when the unit is transmitting.

High Filter

The high-frequency-cut filter acts to improve readability in congested areas etc., eliminating high frequency noise component in audio output. In PTSW072 circuit board, Q702 serves to compensate CR filter loss.

Power Supply

The supplied 220V AC is stepped down through T201 and rectified by bridge rectifiers D1 to 4 on PTPW007. When the voltage output at pin #3 on the circuit board decreases, the collector current of Q2 also decreases causing reduced collector voltage. This will increase Q1 bias and Q201 bias. The voltage across the collector to emitter of Q201 decreases thus restoring the initial voltage incline.

Adjustment

Test Equipment

The following equipment are required for servicing:

1. A 50 Ohm resistive antenna load, 20W.
2. A frequency counter operable in the required range.
3. A HF signal generator operable over 50 kHz to 60 MHz.
4. An oscilloscope.
5. An FM deviation meter.
6. A digital Voltmeter.
7. An 8 Ohm 5W resistive speaker load.
8. Two audio signal generators, 10 Hz to 20 kHz.
9. An RF Voltmeter.
10. A circuit tester, input impedance 20 kOhm/V.
11. A 220V 50 Hz AC power source.
12. Dummy microphone plug (wired as shown beside applicable set-up).

To activate the transmitter without using the microphone PTT bar, use the dummy plug. This plug is also used to introduce a modulating audio signal to the microphone input circuit as described in the following procedures.

Precautions

Before performing any adjustment, check visually all jacks, plugs and solder joints for normal connection. Shown in the schematic diagram are nominal tested voltage values for the transistors and ICs. For tune-up and servicing, be sure to use identical parts as listed in the *Replacement Part List*.

Power Supply Alignment


Important: This alignment should be performed first of all items.

- 1) Connect circuit tester across the terminal #3 (plus) and G (minus) on PTPW007.

- 2) Turn unit on at 220V 50 Hz input.
- 3) Reading should be 13.8 Volt. If necessary adjust, RV1.

Transmitter Alignment

Connect testing equipment to the unit as shown:



PLL Alignment (PTOS006)

- 1) Connect frequency counter to TP1 (or IC1 pin #3) through 1,000 pF capacitor.
- 2) Adjust CT1 for 10.240 MHz. Tolerance within ± 50 Hz is acceptable.

Off-Set Frequency Alignment (PTOS006, unless otherwise noted)

- 1) Connect frequency counter to TP4, with maximum level range.
- 2) Set the Mode selector to *USB*.
- 3) Set the Band selector to *Lo*.
- 4) Adjust CT2 for 20.105 MHz ± 40 Hz.
- 5) Set the Band selector to *Mid*.
- 6) Adjust CT3 for 20.330 MHz ± 40 Hz.
- 7) Set the Band selector to *Hi*.
- 8) Adjust CT4 for 20.555 MHz ± 40 Hz.
- 9) Set the Band selector to *Mid*, the Channel selector to 60.
- 10) Connect scope to TP4.
- 11) Adjust T1 for maximum scope amplitude.
- 12) Connect frequency to TP5 (PTBM058).
- 13) Adjust CT5 (PTBM059) for 10.695 MHz ± 50 Hz.

LSB Off-Set Alignment

- 1) Set the Mode selector to *LSB*, the Band selector to *Lo*.
- 2) Connect frequency counter to TP4 (PTOS006).
- 3) Adjust CT5 (PTOS006) for 20.1035 MHz ± 40 Hz.
- 4) Connect frequency counter to TP5 (PTBM059).
- 5) Adjust CT4 for 10.692 MHz ± 50 Hz.

VCO Alignment

- 1) Set the Band selector to *Lo* and the Channel selector to 1.
- 2) Connect digital Voltmeter between TP2 and ground.
- 3) Adjust VCO block core to obtain 3.6V ± 0.1 V.
- 4) Set the Channel selector to 41, and the Band selector to *Mid*.
- 5) Adjust VR1 for 3.7V ± 0.1 V.
- 6) Set the Channel selector to 1, and the Band selector to *Hi* (81 channel).
- 7) Adjust VR2 for 3.8V ± 0.1 V.

RF Power Amplifier Alignment (PTBM058, unless otherwise noted)

- 1) Set the Band selector to *Lo* and the Channel selector to 1.
- 2) Set the Mode switch to *USB*.
- 3) Feed 2,400 Hz 10 mV audio to unit.
- 4) Adjust T3 (PTOS006) and T5 (PTBM058) for maximum scope display.
- 5) Set the Band selector to *Hi* and the Channel selector to 40 (120 channel).
- 6) Adjust T2 (PTOS006) and T4 (PTBM058) for maximum scope display.

RF Driver Alignment (PTBM058)

- 1) Set the Channel selector to 60 with the Band selector set to *Mid*.
- 2) Feed 2,400 Hz 10 mV audio to unit.
- 3) Adjust T6, L11, L12 and L13 for maximum output on RF Wattmeter.
- 4) Remove testing audio.
- 5) Adjust RV4 and RV5 for minimum carrier leakage on scope.

Two-Tone Alignment (Refer to next page diagram)

- 1) Feed 500 Hz and 2,400 Hz audio tones to the mic circuit simultaneously. Use two audio signal generator sets.
- 2) Adjust both testing audio levels by means of attenuators on the generators, so that the scope presents wave figure like shown as 'A' of diagram next page.
- 3) Adjust RV11 to obtain 12W PEP power output.

AM/FM RF Power Alignment

- 1) Set Mode switch to AM, TX mode, channel 60.
- 2) Set RF Power switch to 0.5W.
- 3) Adjust RV9 to 0.5W on Wattmeter.
- 4) Set RF Power switch to 4W.
- 5) Adjust RV8 to 4W on Wattmeter.

AM Modulation Alignment

- 1) Apply 2,400 Hz 7 mV audio to the unit microphone input.
- 2) Adjust RV12 for modulation depth of 80%.
- 3) Increase audio level to 70 mV.
- 4) Check modulation depth increases to 90%.

FM Modulation Alignment

- 1) Set the Mode switch to *FM* position.
- 2) Apply 2,400 Hz 10 mV audio to modulation circuit. Use dummy mic plug.
- 3) Connect deviation meter to antenna output on the unit.
- 4) Adjust RV3 (PTOS006) to obtain 1.5 kHz deviation.

RF Power Meter Alignment


- 1) Set the unit to *AM* mode.
- 2) Comparing the external RF power meter and the one built-in the unit, adjust RV3 (PTBM059) for equal indication on the unit power meter.

Transmitting Frequency Check

Verify that the frequency counter indicates channel frequencies tabulated in the *Frequency Table* with tolerance within ± 800 Hz.

Receiver Alignment

Connect testing equipment as shown:



AGC Alignment

- 1) Connect digital Voltmeter to circuit board PTBM059 terminal 15 (Q20, Q22 AGC input) and chassis ground.
- 2) Set the transceiver to channel 60.
- 3) Rotate the RF Gain control fully clockwise.
- 4) Adjust RV8 for 2V reading.

AM Receiver Sensitivity

- 1) Set the signal generator to 27.655 MHz with 1 kHz 30% modulation.
 - 2) Set the transceiver tuned to channel 60.
 - 3) Set the Mode selector to AM position.
 - 4) Adjust T7, T8, T9, T10, T13, T14 and T15 for maximum audio output across speaker dummy resistor.
- Note: Keep generator output as low as possible to avoid AGC action through this alignment.*
- 5) After completing above procedure, rotate T7 to decrease the audio output by 2 dB.


Squelch Alignment

- 1) Set the Mode selector to AM position.
- 2) Set the signal generator to provide RF input signal of 300 μ V 1 kHz 30% modulated and rotate the Squelch control to the fully clockwise position.
- 3) Adjust RV9 so that the audio appears on scope.


S-Meter Alignment

- 1) Set the Mode switch to AM position.
- 2) Select channel 60 (Mid band).
- 3) Set the signal generator to provide 100 μ V (40 dB) output.
- 4) Adjust RV7 so that the S-meter pointer indicates '9'.


A. Properly adjusted transmitter.




B. Unequal tones – Adjust generator outputs to balance.




C. Excessive modulation – Adjust RV11 counterclockwise.




D. Final transistor incorrectly biased – Adjust VR1.



E. Undermodulation – Adjust RV11 clockwise.




F. Similar to A but showing hum – Check for proper testing condition.




Frequency Table

LOW CHANNEL	CHANNEL FREQUENCY IN MHZ	MID CHANNEL	CHANNEL FREQUENCY IN MHZ	HIGH CHANNEL	CHANNEL FREQUENCY IN MHZ
1	26.965	41	27.415	1	27.865
2	26.975	42	27.425	2	27.875
3	26.985	43	27.435	3	27.885
4	27.005	44	27.455	4	27.905
5	27.015	45	27.465	5	27.915
6	27.025	46	27.475	6	27.925
7	27.035	47	27.485	7	27.935
8	27.055	48	27.505	8	27.955
9	27.065	49	27.515	9	27.965
10	27.075	50	27.525	10	27.975
11	27.085	51	27.535	11	27.985
12	27.105	52	27.555	12	28.005
13	27.115	53	27.565	13	28.015
14	27.125	54	27.575	14	28.025
15	27.135	55	27.585	15	28.035
16	27.155	56	27.605	16	28.055
17	27.165	57	27.615	17	28.065
18	27.175	58	27.625	18	28.075
19	27.185	59	27.635	19	28.085
20	27.205	60	27.655	20	28.105
21	27.215	61	27.665	21	28.115
22	27.225	62	27.675	22	28.125
23	27.255	63	27.705	23	28.155
24	27.235	64	27.685	24	28.135
25	27.245	65	27.695	25	28.145
26	27.265	66	27.715	26	28.165
27	27.275	67	27.725	27	28.175
28	27.285	68	27.735	28	28.185
29	27.295	69	27.745	29	28.195
30	27.305	70	27.755	30	28.205
31	27.315	71	27.765	31	28.215
32	27.325	72	27.775	32	28.225
33	27.335	73	27.785	33	28.235
34	27.345	74	27.795	34	28.245
35	27.355	75	27.805	35	28.255
36	27.365	76	27.815	36	28.265
37	27.375	77	27.825	37	28.275
38	27.385	78	27.835	38	28.285
39	27.395	79	27.845	39	28.295
40	27.405	80	27.855	40	28.305


PC Boards




PTBM059COX




PTPW007COX





PTSW076AOX




PTLD061AOX




PTSW072COX
TPS14-S



PTZZ024AOX





Replacement Part List

PART NAME FLEC. ELEMENTS		PART CODE SRA35AESHL1						
PART CODE	STOCK NUMBER	PART NAME	SPECIFICATIONS			SYMBOLIC OR EXPLODED VIEW NO.		Q'TY USED
ACAC0041EEA		AC CORD ASSY.				AC1		1
ACCN038GFA		CONN CORD ASSY.				J7		1
APTRM059CA		P.W. BOARD ASSY.						1
APTL0061AA		P.W. BOARD ASSY.						1
APTPW007FA		P.W. BOARD ASSY.						1
APTSR017RA		P.W. BOARD ASSY.						1
APTSW026QA		P.W. BOARD ASSY.						1
APTSW072BA		P.W. BOARD ASSY.						1
APTSW074AA		P.W. BOARD ASSY.						1
APTZZ0GRP1		P.W. BOARD ASSY.						1
APTZZD24BA		P.W. BOARD ASSY.						1
APTOS004CA		P.W. BOARD ASSY.						1
CCDR390KPM		CERAMIC CAP.	39PF	50V	-10, +10% PH	C201	C202	C204
CEAF4P7AIX		FLYLT. CAPACITOR	4.7MF	25V		C212		1
CK081039EM		CERAMIC CAP.	0.01MF	50V	-0, +10% E	C205		1
CKD84737FM		CERAMIC CAP.	0.047MF	50V	-20, +20% F	C203		1
GUJUMB0-A03		WIRE KIT						1
ODCTT31X0		VARI-CAP. DIODE	1TT310	12V	NO-RANK 25MIN	D206		1
ODSM1150XN		SILICON DIODE	MA150	VF=1.2V, VR=35V	ND-RANK 24MIN	D201	D202	D203
						D205		
OLAP3139SR		I.E.D.	GD4-209RD RFD	1.7V		PL3		1
OTD0704XAF		TRANSISTOR	2SD704	D, F-RANK		D201		1
OD25TJ104X		CARBON FILM R.	0.25W	100K OHM	5%	R207		1

PART NAME FLEC. ELEMENTS		PART CODE SRA35AESHL1						
PART CODE	STOCK NUMBER	PART NAME	SPECIFICATIONS			SYMBOLIC OR EXPLODED VIEW NO.		Q'TY USED
OD25TJ153X		CARBON FILM R.	0.25W	15K OHM	5%	R206		1
OD25TJ193X		CARBON FILM R.	0.25W	19K OHM	5%	R209		1
OD25TJ223X		CARBON FILM R.	0.25W	22K OHM	5%	R205	R210	2
OD25TJ473X		CARBON FILM R.	0.25W	47K OHM	5%	R204		1
OD25TJ562X		CARBON FILM R.	0.25W	5.6K OHM	5%	R202		1
OD25TJ563X		CARBON FILM R.	0.25W	56K OHM	5%	R203		1
OD25TJ683X		CARBON FILM R.	0.25W	68K OHM	5%	R208		1
OG1AN1540R		M-OXIDE FILM R.	1W	56 OHM	5%	R201		1
PVNA502A05		VR.				VR3		1
PVNA502A13		VR.				VR1	VR2	2
PVNA503913		VR.				VR5		1
PVNL03P02		VR.				VR7		1
PVH12503A02		V.P.				VR4	VR6	2
PWVA060B02		VR.	6 OHM A-CURVE			VR8		1
SL020201CA		LEVEL SWITCH				S1		1
SP04021024		ROTARY SWITCH				S2		1
SP0403107H		ROTARY SWITCH				S4		1
SP0604207H		ROTARY SW				S3		1
TPJ74E001Y		PWR. TRANSFORMER				T201		1
VM270NB005		BUSHING				ACB1		1
YHF152001D		FUSE HOLDER						1
YJC025015Z		ANT JACK				J1	J2	2
YJS03S019Z		PHONE JACK				J5		1

PART NAME MECH. ELEMENTS		PART CODE SR135A5SHL2		SPECIFICATIONS					SYMBOLIC OR EXPLODED VIEW NO.					Q'TY USED	
PART CODE	STOCK NUMBER	PART NAME													
AMJUMBO-02		ESCHUTCHON ASSY						1							1
4SPB425D4NN		BIND HEAD SCREW (+)BIT, M2.5 X 4 S-NI						B19-1	B18-2						2
4SPB320DANN		BIND HEAD SCREW (+)BIT, M3 X 6 S-NI						B17-1	B17-2	B33					3
4SPB430DANN		BIND HEAD SCREW (+)BIT, M3 X 8 S-NI						B38							1
4SPB571DNG		BIND HEAD SCREW (+)BIT, M5 X 10 S-BLACK						B19-1	B19-2	B19-3	B19-4				8
								B40-1	B40-2	B40-3	B40-4				
4SPC320DANZ		CEMS SCREW (+)BIT, M3 X 6 S-ZNCR						B16-1	B16-2	B16-3	B16-4				9
								B16-5	B16-6	B16-7	B16-8				
								B16-9							
4SPF300ANR		BIND NAIL SCREW (+)BIT, M3 X 6 S-BLACK						B27-1	B27-2	B27-3	B28-1				5
								B28-2							
4SPD300ANT		PAN HEAD SCREW (+)BIT, M3 X 6 PLASTIC						B30-1	B30-2	B30-3	B30-4				5
								B30-5							
4SPS300ENV		FLAT HEAD SCREW (+)BIT, M3 X 5 S-NI						B26-1	B26-2	B26-3					3
4SPS5712NRA		FLAT HEAD SCREW (+)BIT, M5 X 12 S-BLACK						B41-1	B41-2	B41-3	B41-4				4
4TP4400PTZ		BIND TAP SCREW (+)BIT, M4 X 8 S-ZNCR (TAP TITE)						B20-1	B20-2	B20-3	B20-4				8
								B21-1	B21-2	B21-3	B21-4				
4TP4300BRB		NATL TAP SCREW (+)BIT, M3 X 8 S-BLACK						B25-1	B25-2	B25-3	B25-4				4
4TPP304FRZ		PAN TAP SCREW (+)BIT, M3 X 45 S-ZNCR						B29-1	B29-2						2
4TPW3C0RHB		BRAS. TAP SCREW (+)BIT, M3 X 8 S-BLACK						B15-1	B15-2						2
4TPW3C0RBJ		BRAS. TAP SCREW						B13-1	B13-2	B13-3	B13-4				5
								B14							
4TPW300BRZ		BRAS. TAP SCREW (+)BIT, M3 X 8 S-ZNCR						B1-1	B1-2	B1-3	B1-4				47

PART NAME MECH. ELEMENTS		PART CODE SRA35AESHL2	SPECIFICATIONS					SYMBOLIC OR EXPLODED VIEW NO.				Q'TY USED
PART CODE	STOCK NUMBER	PART NAME						B10	B11-1	B11-2	B11-3	
								B11-4	B11-5	B11-6	B11-7	
								B11-8	B2-1	B2-2	B2-3	
								B2-4	B2-5	B2-6	B2-7	
								B2-8	B3-1	B3-2	B3-4	
								B35-1	B35-2	B35-3	B35-4	
								B36	B37-1	B37-2	B4-1	
								B4-2	B5-1	B5-2	B5-3	
								B5-4	B5-5	B5-6	B6-1	
								B6-2	B6-3	B6-4	B7	
								B9	B9-1	B9-2		
4TP6301407		4RAS. TAP SCREW	(+)	BIT, M3 X 14	S-ZNCR			B12-1	B12-2	B12-3	B12-4	4
4TPX320007		T.T BT SCREW	(+)	BIT, M3 X 8	S-ZNCR			B22-1	B22-2	B22-3	B22-4	13
								B22-5	B23-1	B23-2	B23-3	
								B23-4	B24-1	B24-2	B39-1	
								B39-2				
3W43200557		FLAT L. WASHER	FLAT LARGE,	3	M/M	S-ZNCR		B31-1	B31-2	B31-3	B31-4	4
5445700058		FLAT L. WASHER	FLAT LARGE,	5	M/M	S-BLACK		B32-1	B32-2	B32-3	B32-4	8
								B42-1	B42-2	B42-3	B42-4	
4337452003		FRONT PANEL						5				1
4B38252001		CHASSIS						2				1
4B972SF099		REAR PANEL						6				1
4C24150001		BRACKET						11				1

PART NAME ACCH. ELEMENTS		PART CODE SRA35AFSHL?		SPECIFICATIONS				SYMBOLIC OR EXPLODED VIEW NO.				Q'TY USED
PART CODE	STOCK NUMBER	PART NAME										
M471SZ002		BRACKET						36-1	36-2			2
M360SF003		SCUTCHEPN						8				1
M1215Z004		BRACKET						19-1	19-2	19-3	19-4	4
M1225Z011		L ANGLE						39				1
M1622BN001		TERMINAL						14				1
M17447M001		BRACKET						42-1	42-2			2
MN2767A119		KNOB VR						13-1	13-10	13-2	13-3	10
								13-4	13-5	13-6	13-7	
								13-8	13-9			
MN385AM020		TUNER KNOB						12				1
MS1225Z001		BRACKET						40-1	40-2			2
M53865Z041		BOTTOM PLATE						10				1
MT213BD015		SUPPORT						15				1
MJ2747M001		HANDLE						41-1	41-2			2
M1351SZ002		BRACKET L						3				1
MJ351SZ003		BRACKET R						4				1
MJ654AD002		HEAT SINK						17				1
MJ362SZ008		BRACKET						7				1
MJ397SM010		COVER						9				1
MX615SZ002		CLAMPER						33-1	33-2	33-3		3
V9532AW001		LAMP HOUSE						21-1	21-2			2
VF164DN003		BUSHING						38				1
VF176DN002		WASHER						31-1	31-2			2

PART NAME P.W.B BOARD ASSY.	PART CODE APTRM059CA								
PART CODE	STOCK NUMBER	PART NAME	SPECIFICATIONS			SYMBOLIC OR EXPLODED VIEW NO.			Q'TY USED
BHNCL25NBN		NJT	M2.6	RS-NI	THIN-TYPE				2
BSPPB3006NN		BLIND HEAD SCREW	(+1)BIT, M3	X 6	S-NI				7
BSPPB3006NT		PAN HEAD SCREW	(+1)BIT, M3	X 6	PLASTIC				3
BWU26587SW		IT. LOCK WASHER	INSIDE TOOTHED,	2.6M/M	S-ZN				2
BWU30655SW		IT. LOCK WASHER	INSIDE TOOTHED,	3	M/M S-ZN				5
CCCB020CPM		CERAMIC CAP.	PK	2PF	50V	-0.25	, +0.25PF	C61	1
CCCB030CPM		CERAMIC CAP.	PJ	3PF	50V	-0.25	, +0.25PF	C104	1
CCCB050CPM		CERAMIC CAP.	PH	5PF	50V	-0.25	, +0.25PF	C42	C60
CCCB050DPM		CERAMIC CAP.	PH	5PF	50V	-0.5	, +0.5PF	C112	C140
CCCB050DPM		CERAMIC CAP.	PH	6PF	50V	-0.5	, +0.5PF	C95	
CCCB080DPM		CERAMIC CAP.	PH	8PF	50V	-0.5	, +0.5PF	C71	1
CCCB100CH		CERAMIC CAP.	CH	10PF	50V	-0.5	, +0.5PF	C66	1
CCCB101KPM		CERAMIC CAP.		100PF	50V	-10	, +10% PH	C138	C72
CCCR101KOM		CERAMIC CAP.		100PF	50V	-10	, +10% SL	C194	1
CCCR151KPM		CERAMIC CAP.		150PF	50V	-10	, +10% PH	C36	C54
CCCB151KOM		CERAMIC CAP.		150PF	50V	-10	, +10% SL	C156	
CCCB180KPM		CERAMIC CAP.		18PF	50V	-10	, +10% PH	C147	C188
CCCB220KPM		CERAMIC CAP.		22PF	50V	-10	, +10% PH	C139	C68
CCCB221KPM		CERAMIC CAP.		220PF	50V	-10	, +10% PH	C113	C186
								C53	C69
								C70	
CCCB221KOM		CERAMIC CAP.		220PF	50V	-10	, +10% SL	C133	C153
CCCB270KPM		CERAMIC CAP.		27PF	50V	-10	, +10% PH	C122	
CCCB271KOM		CERAMIC CAP.		270PF	50V	-10	, +10% SL	C184	

PART NAME P.W. BOARD ASSY. APTBMO59CA		PART CODE		SPECIFICATIONS				SYMBOLIC OR EXPLODED VIEW NO.				Q'TY USED
PART CODE	STOCK NUMBER	PART NAME		33PF	50V	-10, +10%	PH	C100	C12	C73	C96	
CCCB330KPM		CERAMIC CAP.		33PF	50V	-10, +10%	PH	C100	C12	C73	C96	4
CCCB390KCM		CERAMIC CAP.		39PF	50V	-10, +10%	CH	C65				1
CCCB390KPM		CERAMIC CAP.		39PF	50V	-10, +10%	PH	C107	C185			2
CCCB391KOM		CERAMIC CAP.		390PF	50V	-10, +10%	SL	C49				1
CCCB470KPM		CERAMIC CAP.		47PF	50V	-10, +10%	PH	C43	C47	C56		3
CCCB471KOM		CERAMIC CAP.		470PF	50V	-10, +10%	SL	C57				1
CCCB551KOM		CERAMIC CAP.		560PF	50V	-10, +10%	SL	C55				1
CCCB680KOM		CERAMIC CAP.		68PF	50V	-10, +10%	SL	C157	C159			2
CCCB820KOM		CERAMIC CAP.		82PF	50V	-10, +10%	PH	C37	C52			2
CCDR561KOM		CERAMIC CAP.		56PF	50V	-10, +10%	PH	C38				1
CEAB330ALX		FLYT. CAPACITOR		33MFD	6.3V			C160	C97			2
CEAB470ALX		FLYT. CAPACITOR		47MFD	6.3V			C171				1
CEAC470ALX		FLYT. CAPACITOR		47MFD	10V			C148				1
CEAD100ALX		FLYT. CAPACITOR		100MFD	16V			C119	C145	C80		3
CEAD101ALX		FLYT. CAPACITOR		100MFD	16V			C168				1
CEAD222ALX		FLYT. CAPACITOR		2200MFD	16V			C166				1
CEAD320ALX		FLYT. CAPACITOR		33MFD	16V			C178				1
CEAD331ALX		FLYT. CAPACITOR		330MFD	16V			C167				1
CEAD470ALX		FLYT. CAPACITOR		47MFD	16V			C162	C176	C179		3
CEAF252ALX		FLYT. CAPACITOR		2.2MFD	25V			C175				1
CEAF340ALX		FLYT. CAPACITOR		3.3MFD	25V			C129	C142			2
CEAF407ALX		FLYT. CAPACITOR		4.7MFD	25V			C131	C150			2
CEAF474ALX		FLYT. CAPACITOR		0.47MFD	50V			C170	C182			2

PART NAME P.W. BOARD ASSY. APTBMO59CA		PART CODE		SPECIFICATIONS				SYMBOLIC OR EXPLODED VIEW NO.				Q'TY USED
PART CODE	PART, STOCK NUMBER	PART NAME		1MFD	50V			C108	C135	C164	C173	
CEAD100ALX		FLYT. CAPACITOR		1MFD	50V			C108	C135	C164	C173	5
								C63				
CECH222KHM		CERAMIC CAP.		2200PF	50V	-10, +10%	3	C197				1
CECB471ZEM		CERAMIC CAP.		0.047MFD	50V	-20, +20%	F	C165	C180	C181	C189	4
CECB473ZEM		CERAMIC CAP.		0.047MFD	50V	-20, +20%	F	C198	C902			2
COMB100KCH		MYLAR CAPACITOR		1000PF	50V	-10, +10%		C115	C121	C183	C67	5
								C98				
COMB102KCH		MYLAR CAPACITOR		0.01MFD	50V	-10, +10%		C101	C103	C105	C106	48
								C109	C110	C111	C118	
								C124	C126	C136	C137	
								C144	C146	C149	C156	
								C169	C172	C174	C199	
								C191	C35	C39	C40	
								C45	C46	C48	C50	
								C59	C62	C64	C75	
								C77	C79	C81	C82	
								C83	C84	C85	C86	
								C88	C89	C90	C91	
								C92	C93	C94	C99	
COMB222KCH		MYLAR CAPACITOR		2200PF	50V	-10, +10%		C151	C155	C195		3
COMB223KCH		MYLAR CAPACITOR		0.022MFD	50V	-10, +10%		C152				1
COMB373KCH		MYLAR CAPACITOR		0.033MFD	50V	-10, +10%		C116	C123	C125	C130	4
COMB472KCH		MYLAR CAPACITOR		4700PF	50V	-10, +10%		C114	C117	C128	C132	4

PART NAME P.W. BOARD ASSY.	PART CODE APTBM059CA		SPECIFICATIONS	SYMBOLIC OR EXPLODED VIEW NO.		Q'TY USED
PART CODE	STOCK NUMBER	PART NAME				
TR10CA006T		RF COIL		T4	T8	2
TR10CR001S		RF COIL		T9		1
TR10CR003T		P.F.T.		T5		1
TR10CP006S		RF COIL		T6		1
TR10CZ003S		RF COIL		T7		1
TR10CZ004S		RF COIL		T13		1
TR10CZ005S		RF COIL		T11		1
TR10LA001S		I.F.T.		T14		1
TR10LA002S		I.F.T.		T15		1
TR10MA013S		I.F.T.		T10		1
TR10MA014S		I.F.T.		T13		1
TR10MA015S		I.F.T.		T11	T12	2
TR10MD003T		RF COIL		T7		1
VK111SC001		SPACER				1
VS222PH002		SILICON SHEET				2
VS311XX001		BARRIER				1
WD48152001		COAXIAL CABLE		3		1
WD48172001		COAXIAL CABLE		4		1
WJG113EFXX		HI-WRAP WIRE		33		1
WJG210EFXX		HI-WRAP WIRE		12	22	2
WJG213EFXX		HI-WRAP WIRE		21	30	2
WJG209EFXX		HI-WRAP WIRE		15	36	2
WJG216EFXX		HI-WRAP WIRE		25	32	2

PART NAME P.W. BOARD ASSY.		PART CODE APTBMO59CA		SPECIFICATIONS				SYMBOLIC OR EXPLODED VIEW NO.				Q'TY USED
PART CODE	STOCK NUMBER	PART NAME						D40	D41	D42	D44	
								D45	D46	D47	D48	
								D49	D52	D53	D6	
								D8				
00551885XT		SILICON DIODE	1S1185 VRM=100 VFM=1.2 25MIN		D51							1
00ZMZ305CE		ZENER DIODE			D7							1
00ZMZ310XE		ZENER DIODE	MZ310	NJ-RANK	D50							1
00MAN612AN		I.C.	AN612 7-PIN BALANCED-MOD.		IC4							1
00MC3001AN		I.C.	AN103 D-RANK C3001-D		IC3							1
02407205RT		I.C.	TA7205APS-BW AUDIO-POWER-AMP		IC5							1
0TA0688XRN		TRANSISTOR	2SA683 R-RANK		Q40	Q42						2
0TA0719XAN		TRANSISTOR	2SA719 Q-RANK		Q37	Q38						2
0TA0733XAA		TRANSISTOR	2SA733 Q-RANK		Q25	Q32						2
0TC0460XRR		TRANSISTOR	2SC460 A,B-RANK		Q8							1
0TC0710XAF		TRANSISTOR	2SC710 C-RANK		Q13	Q14	Q15	Q16				10
					Q17	Q20	Q22	Q27				
					Q29	Q45						
0TC0710XBF		TRANSISTOR	2SC710 D-RANK		Q11	Q12	Q18	Q21				6
					Q29	Q7						
0TC0763XAE		TRANSISTOR	2SC763 C,D-RANK		Q23	Q26						2
0TC0900YCA		TRANSISTOR	2SC900 U-RANK		Q35							1
0TC0945ABA		TRANSISTOR	2SC945A Q-RANK		Q19	Q31	Q33	Q34				6
					Q36	Q39						

PART NAME P.W. BOARD ASSY.		PART CODE APTBMO59CA		SPECIFICATIONS				SYMBOLIC OR EXPLODED VIEW NO.				Q'TY USED
PART CODE	STOCK NUMBER	PART NAME						R41	R43			
0TC1332XAN		TRANSISTOR	2SC1383 R-RANK		R41	R43						2
0TC1469XAF		TRANSISTOR	2SC1969 X,D-RANK		R10							1
0TC2156YMF		TRANSISTOR	2SC2166 N,D-RANK		R9							1
0TD0325XCF		TRANSISTOR	2SD325 D,E-RANK		R44							1
0TK0034YAF		TRANSISTOR	2SK34 C,D-RANK		R24							1
0TK0034YBE		TRANSISTOR	2SK34 E-RANK		R30							1
0225VJ100X		CARBON FILM R.	0.25W 10 OHM 5%		R34	R38						2
0225VJ101X		CARBON FILM R.	0.25W 100 OHM 5%		R29	R39	R68	R73				4
0225VJ102X		CARBON FILM R.	0.25W 1K OHM 5%		R120	R123	R127	R137				12
					R140	R146	R166	R47				
					R54	R77	R80	R90				
0225VJ103X		CARBON FILM R.	0.25W 10K OHM 5%		R108	R119	R124	R125				10
					R132	R139	R31	R45				
					R92	R98						
0225VJ104X		CARBON FILM R.	0.25W 100K OHM 5%		R50	R75	R89	R96				4
0225VJ105X		CARBON FILM R.	0.25W 1M OHM 5%		R121	R97						2
0225VJ121X		CARBON FILM R.	0.25W 120 OHM 5%		R53							1
0225VJ122X		CARBON FILM R.	0.25W 12K OHM 5%		R57	R79						2
0225VJ151X		CARBON FILM R.	0.25W 150 OHM 5%		R109	R138	R60	R72				4
0225VJ152X		CARBON FILM R.	0.25W 1.5K OHM 5%		R27	R71						2
0225VJ153X		CARBON FILM R.	0.25W 15K OHM 5%		R70	R74						2
0225VJ155X		CARBON FILM R.	0.25W 1.5M OHM 5%		R93							1
0225VJ193X		CARBON FILM R.	0.25W 19K OHM 5%		R44	R67						2

PART NAME P.W. BOARD ASSY.		PART CODE APT8M059CA						
PART CODE	STOCK NUMBER	PART NAME	SPECIFICATIONS			SYMBOLIC OR EXPLODED VIEW NO.		Q'TY USED
R025VJ221X		CARBON FILM R.	0.25W 220 OHM 5%	R32	R64	R83	R87	4
R025VJ222X		CARBON FILM R.	0.25W 2.2K OHM 5%	R106	R126	R142	R143	4
R025VJ223X		CARBON FILM R.	0.25W 22K OHM 5%	R113	R128	R133		3
R025VJ271X		CARBON FILM R.	0.25W 270 OHM 5%	R175	R36			2
R025VJ272X		CARBON FILM R.	0.25W 2.7K OHM 5%	R151	R152	R153	R154	6
				R155	R156			
R025VJ273X		CARBON FILM R.	0.25W 27K OHM 5%	R129				1
R025VJ274X		CARBON FILM R.	0.25W 270K OHM 5%	R115				1
R025VJ330X		CARBON FILM R.	0.25W 33 OHM 5%	R35				1
R025VJ331X		CARBON FILM R.	0.25W 330 OHM 5%	R100	R48	R51		3
R025VJ332X		CARBON FILM R.	0.25W 3.3K OHM 5%	R145	R147	R172	R43	11
				R52	R58	R59	R69	
				R78	R84	R88		
R025VJ333X		CARBON FILM R.	0.25W 33K OHM 5%	R110	R116	R41		3
R025VJ391X		CARBON FILM R.	0.25W 390 OHM 5%	R159				1
R025VJ393X		CARBON FILM R.	0.25W 39K OHM 5%	R107				1
R025VJ470X		CARBON FILM R.	0.25W 47 OHM 5%	R111	R112	R136		3
R025VJ471X		CARBON FILM R.	0.25W 470 OHM 5%	R103	R66	R86		3
R025VJ472X		CARBON FILM R.	0.25W 4.7K OHM 5%	R141	R40	R62	R65	6
				R81	R85			
R025VJ473X		CARBON FILM R.	0.25W 47K OHM 5%	R114	R118	R49	R82	4
R025VJ474X		CARBON FILM R.	0.25W 470K OHM 5%	R91				1
R025VJ561X		CARBON FILM R.	0.25W 560 OHM 5%	R105	R134	R46	R55	5

PART NAME P.W. BOARD ASSY.		PART CODE APT8M059CA						
PART CODE	STOCK NUMBER	PART NAME	SPECIFICATIONS			SYMBOLIC OR EXPLODED VIEW NO.		Q'TY USED
				R63				
R025VJ562X		CARBON FILM R.	0.25W 5.6K OHM 5%	R102	R104	R130	R131	9
				R168	R56	R94	R95	
				R99				
R025VJ563X		CARBON FILM R.	0.25W 55K OHM 5%	R101				1
R025VJ680X		CARBON FILM R.	0.25W 68 OHM 5%	R33				1
R025VJ691X		CARBON FILM R.	0.25W 690 OHM 5%	R122	R42			2
R025VJ692X		CARBON FILM R.	0.25W 6.9K OHM 5%	R144				1
R025VJ693X		CARBON FILM R.	0.25W 68K OHM 5%	R117				1
R025VJ821X		CARBON FILM R.	0.25W 820 OHM 5%	R135	R61			2
R025VJ822X		CARBON FILM R.	0.25W 8.2K OHM 5%	R30				1
RGHANJ391R		M-OXIDE FILM R.	1/2W 390 OHM 5%	R157				1
RGHANJ51R		M-OXIDE FILM R.	1/2W 560 OHM 5%	R37				1
PPGNR10201		SEMI-FIXED VR.	1K OHM B-CURVE	RV4				1
PPGNR10201		SEMI-FIXED VR.	10K OHM B-CURVE	RV5	RV7			2
PPGNR20201		SEMI-FIXED VR.	2K OHM B-CURVE	RV12				1
PPGNR20201		SEMI-FIXED VR.	20K OHM B-CURVE	RV3	RV6	RV9		3
PPGNR20401		SEMI-FIXED VR.	200K OHM B-CURVE	RV10				1
PPGNR50101		SEMI-FIXED VR.	500 OHM B-CURVE	RV11				1
PPGNR50201		SEMI-FIXED VR.	5K OHM B-CURVE	RV2	RV8			2
RPNB10101		SEMI-FIXED VR.	100 OHM B-CURVE	RV1				1
RX2ANJ1808		M-OXIDE FILM R.	2W 18 OHM 5%	R150				1
TBG29A004W		AF OPT		TL6				1

PART NAME P.W. BOARD ASSY.	PART CODE APTBMO59CA		SPECIFICATIONS				SYMBOLIC OR EXPLODED VIEW NO.			Q'TY USED
PART CODE	STOCK NUMBER	PART NAME								
COMB473KCH		MYLAR CAPACITOR	0.047MFD	50V	-10, +10%		C102	C192	C51	3
COMB683KCH		MYLAR CAPACITOR	0.068MFD	50V	-10, +10%		C161			1
COMB922KCH		MYLAR CAPACITOR	8200PF	50V	-10, +10%		C134			1
CSSD100MDN		TANTALUM CAP.	10MFD	16V	-20, +20%		C127			1
CSSD100MDC		TANTALUM CAP.	1MFD	25V	-20, +20%		C141	C143		2
CSSE3R9MDC		TANTALUM CAP.	3.9MFD	25V	-20, +20%		C156			1
CSSE3R22MDC		TANTALUM CAP.	0.22MFD	35V	-20, +20%		C58	C76	C78	5
							C901			
CT76200401		TRIMMER CAP.					CT5			1
CT77250401		TRIMMER CAP.					CT4			1
FB2455A13M		MECH.FILTER					CF			1
FF1037501G		M. XTAL FILTER					MXF			1
LA1JG1004A		COIL					L12			1
LB3JE1003A		CHOKE COIL					L20	L21		2
LD0A0A3018J		PF COIL					L6			1
LD0A0A3528G		COIL					L3			1
LD0A0A3524H		P.F.C.					L10	L8		2
LD0A0R4004B		RF COIL					L22	L23	L9	3
LF009KD001N		PEAKING COIL					L16			1
LF102KD001S		RF COIL					L18			1
LF202KD001N		RF COIL					L15	L4	L5	3
LF507KD001N		P.F.C.					L14			1
LF509KD001N		RF COIL					L17	L19	L24	3

Part Name Description Assy.	Part Code Ref ID		Specifications					Symbolic or Exploded View No.			Q'ty Used
Part Code	Stock Number	Part Name									
LJ119H004W		CHOKE COIL					C4				1
WR654SX001		SHIELD									1
ML321AD0001		HEAT SINK									1
ML565AD0071		HEAT SINK									1
MOS31AD0001		HEAT SHINK									1
X5327AD0004		HEAT SINK									1
MW201BS0002		TERMINAL									6
MW201BS0004		TERMINAL									42
M4401CX001		SHORT JUMPER									7
M4401CX002		SHORT JUMPER									2
M4401CX003		SHORT JUMPER									6
M4401CX004		SHORT JUMPER									2
MX653AD0001		HEAT SHINK									1
PR4M159COX		PRINTED W. BOARD									1
DDG146A0XXT		GERMANIUM DIODE NO-RANK				D20	D21	D22	D23		11
						D25	D27	D28	D29		
						D31	D33	D9			
DDG1532XXT		GERMANIUM DIODE LS32 VR=60VNO-RANK 25MIN				D16	D24	D34			3
DDSGP25GXG		SILICON DIODE GP25G 400V NO-RANK				D43					1
DDSM157XN		SILICON DIODE MA150 VF=1.2V,VR=35V NJ-RANK 24MIN				D10	D11	D12	D14		29
						D15	D17	D18	D19		
						D26	D30	D32	D35		
						D36	D37	D38	D39		

PART NAME P.W. BOARD ASSY.	PART CODE APTSW0728A		SPECIFICATIONS				SYMBOLIC OR EXPLODED VIEW NO.			QTY USED
PART CODE	STOCK NUMBER	PART NAME	270PF	50V	-10, +10% SL	C702				1
CCCR271K0M		CERAMIC CAP.	270PF	50V	-10, +10% SL	C702				1
CEFD470A1X		FLYT. CAPACITOR	4.7MFD	16V		C705	C706			2
CEFF3R3A1X		FLYT. CAPACITOR	3.3MFD	25V		C715				1
CEFF4P7A1X		FLYT. CAPACITOR	4.7MFD	25V		C731	C704			2
CEFG0P1ZMN		FLYT. CAPACITOR	0.1MFD	50V	45	C713				1
COMR102KFH		MYLAR CAPACITOR	1000PF	50V	-10, +10%	C703				1
COMR103KHF		MYLAR CAPACITOR	0.01MFD	50V	-10, +10%	C712	C716			2
COMR123KHF		MYLAR CAPACITOR	0.012MFD	50V	-10, +10%	C710				1
COMR153KHF		MYLAR CAPACITOR	0.015MFD	50V	-10, +10%	C709				1
COMR223KHF		MYLAR CAPACITOR	0.022MFD	50V	-10, +10%	C711	C714	C717		3
COMR323KHF		MYLAR CAPACITOR	0.033MFD	50V	-10, +10%	C708				1
COMR222KHF		MYLAR CAPACITOR	8200PF	50V	-10, +10%	C707				1
M2014S003		TERMINAL								26
M401CX001		SHORT JUMPER				J1	J2			2
M401CX003		SHORT JUMPER				J4				1
M401CX004		SHORT JUMPER				J3	J5			2
PTSW072PCX		PRINTED W.BOARD								1
ZG14600XT		GERMANIUM DIODE	NO-RANK			0702	0704			2
DSM150XN		SILICON DIODE	MA150	VF=1.2V, VR=35V	NO-RANK 24MTV	0701				1
DTA0628XAF		TRANSISTOR	2SA628	F-RANK		0704				1
DTCD900XRA		TRANSISTOR	2SC900	F-RANK		0702				1
DTCD945AAA		TRANSISTOR	2SC945A	P-RANK		0703	0707			2
DTCD1312XAF		TRANSISTOR	2SC1312	G-RANK		0701				1

PART NAME P.W. BOARD ASSY.	PART CODE APTO5006CA		SPECIFICATIONS				SYMBOLIC OR EXPLODED VIEW NO.				Q'TY USED
PART CODE	STOCK NUMBER	PART NAME									
CBD1E102KM		CERAMIC CAP.					C16	C18	C25	C39	5
							C40				
CBD1E103KM		CERAMIC CAP.					C34	C37			2
CBD1E122KM		CERAMIC CAP.					C19				1
CBD1E223KM		CERAMIC CAP.					C7				1
CBD1E472KM		CERAMIC CAP.					C38	C6			2
CBD1E473KM		CERAMIC CAP.					C36				1
CCCR020CPM		CERAMIC CAP.	PK	2PF	50V	-0.25, +0.25PF	C35				1
CCCB030CPM		CERAMIC CAP.	PJ	3PF	50V	-0.25, +0.25PF	C20				1
CCCB050CPM		CERAMIC CAP.	PH	5PF	50V	-0.25, +0.25PF	C13				1
CCDR120KPM		CERAMIC CAP.		12PF	50V	-10, +10% PH	C14				1
CCDR150KPM		CERAMIC CAP.		15PF	50V	-10, +10% PH	C21				1
CCDR220KPM		CERAMIC CAP.		22PF	50V	-10, +10% PH	C12				1
CCDR221KPM		CERAMIC CAP.		220PF	50V	-10, +10% PH	C23				1
CCDH530KPM		CERAMIC CAP.		68PF	50V	-10, +10% PH	C10	C17			2
CCDR220KPM		CERAMIC CAP.		82PF	50V	-10, +10% PH	C9				1
CEAR470ALX		FLYT. CAPACITOR		47MFD	6.3V		C4				1
CEAD170ALX		FLYT. CAPACITOR		10MFD	16V		C3	C42			2
CEAD330ALX		FLYT. CAPACITOR		33MFD	16V		C33				1
CEAG010ALX		FLYT. CAPACITOR		1MFD	50V		C28	C32	C41		3
CKD0103KHU		CERAMIC CAP.		0.01MFD	50V	-10, +10% B	C26	C27	C29	C30	4
CKD04737FM		CERAMIC CAP.		0.047MFD	50V	-20, +20% F	C22	C5			2
COMM102KFH		MYLAR CAPACITOR		1000PF	50V	-10, +10%	C8				1

Part Name P.W.B. & ASSY.	Part Code APTO50060A		Specifications					Symbolic or Exploded View No.				Q'Ty Used
Part Code	Stock Number	Part Name										
C0M154KEH		MYLAR CAPACITOR	0.15MFD	50V	-10, +10%		C31					1
C0M8561KEH		MYLAR CAPACITOR	560PF	50V	-10, +10%		C11					1
CSSEF22MDC		TANTALUM CAP.	0.22MFD	35V	-20, +20%		C2					1
CSSEF01MDC		TANTALUM CAP.	0.1MFD	35V	-20, +20%		C1					1
CT26220401		TRIMMER CAP.					CT1	CT2	CT3	CT4		5
							CT5					
LF151KRD1S		RF COIL					L3					1
LF2P2KB02S		RF COIL					L1					1
LF6R0KK01S		RF COIL					L2					1
MW201PS003		TERMINAL										28
MW401CX001		SHORT JUMPER										3
MW401CX003		SHORT JUMPER										2
MW401CX004		SHORT JUMPER										2
PT05006A0X		PRINTED W. BOARD										1
30CTT310X0		VAPI-CAP. DIODE	ITT310	12V	NO-RANK	26MIN	D4	D5	D6			3
30SN4448XZ		SILICON DIODE	IN4448	VRM=100V	NO-RANK		D1	D10	D2	D7		6
								D8	D9			
00ZM7305CE		ZENER DIODE					D3					1
00MAN240PN		I.C.	AN240P				IC3					1
00MC3001AT		I.C.	TA7310P	0-RANK	C3001A-0	9-PIN	IC2					1
000PLL02AN		I.C.	PLL02A	(MN6040)			IC1					1
OTC0710XRE		TRANSISTOR	2SC710	0-RANK			Q2	Q3	Q4	Q5		4
OTC0900XRA		TRANSISTOR	2SC900	E-RANK			Q1					1

PART NAME P.W. BOARD ASSY.		PART CODE APTO5006CA		SPECIFICATIONS				SYMBOLIC OR EXPLODED VIEW NO.			Q'TY USED
PART CODE	STOCK NUMBER	PART NAME									
D700636XBN		TRANSISTOR	2SD636	Q.R-RANK			26	37	08		3
R025VJ101X		CARBON FILM R.	0.25W	100 OHM	5%		826				1
R025VJ102X		CARBON FILM R.	0.25W	1K OHM	5%		815	825			2
R025VJ103X		CARBON FILM R.	0.25W	10K OHM	5%		823				1
R025VJ104X		CARBON FILM R.	0.25W	100K OHM	5%		817	820	98		3
R025VJ105X		CARBON FILM R.	0.25W	1M OHM	5%		83				1
R025VJ153X		CARBON FILM R.	0.25W	15K OHM	5%		819	822			2
R025VJ222X		CARBON FILM R.	0.25W	2.2K OHM	5%		810	827			2
R025VJ223X		CARBON FILM R.	0.25W	22K OHM	5%		821				1
R025VJ272X		CARBON FILM R.	0.25W	2.7K OHM	5%		813				1
R025VJ332X		CARBON FILM R.	0.25W	3.3K OHM	5%		81	824	831	87	4
R025VJ471X		CARBON FILM R.	0.25W	470 OHM	5%		814	816	96		3
R025VJ472X		CARBON FILM R.	0.25W	4.7K OHM	5%		828				1
R025VJ473X		CARBON FILM R.	0.25W	47K OHM	5%		829	830			2
R025VJ474X		CARBON FILM R.	0.25W	470K OHM	5%		84	85			2
R025VJ563X		CARBON FILM R.	0.25W	56K OHM	5%		818				1
R025VJ691X		CARBON FILM R.	0.25W	680 OHM	5%		82				1
R025VJ682X		CARBON FILM R.	0.25W	6.8K OHM	5%		812	837			2
R025VJB20X		CARBON FILM R.	0.25W	82 OHM	5%		811	89			2
RPGNH20201		SEMI-FIXED VR.		2K OHM	B-CURVE		RV3				1
RPGNH20201		SEMI-FIXED VR.		20K OHM	B-CURVE		RV1	RV2			2
T907LA005N		I.F.T.					T4				1
TR07LA023N		I.F.T.					T5				1



BRUSSELSESTEENWEG, 416
B-9218 GENT
BELGIUM
TEL.. 00-32-91-31.21.11
TELEX: 12521 HAM B

©